

Cleanroom Air Shower & Cargo Shower

SUS304 / PAINTED STEEL · HEPA H13 · INTERLOCKED DOORS · 380V 50HZ

KEY SPECIFICATIONS

- Nozzle wind speed 20-25 m/s, adjustable shower time per SOP
- HEPA filters 600x600x120 / 820x600x120, efficiency $\geq 99.995\%$ @0.3um
- Electronically interlocked double doors; auto-sensing blow cycle
- Body options: painted steel plate, SUS304 exterior, full SUS304; custom sizes available

STANDARD MODELS

MODEL	TYPE	EXTERNAL (MM)	INTERNAL (MM)	POWER	NOZZLES	HEPA
BJ900-S-QP-1	1P SINGLE BLOW	1100x1000x2100	800x900x1960	0.55 kW	6	600 x1
BJ900-D-QP-1	1P DOUBLE BLOW	1300x1000x2100	800x900x1960	1.1 kW	12	600 x2
BJ1400-S-QP-2	2P SINGLE BLOW	1100x1500x2100	820x1400x1960	1.0 kW	9	820 x1
BJ1400-D-QP-2	2P DOUBLE BLOW	1300x1500x2100	800x1400x1960	2.0 kW	18	820 x2
BJ1900-D-QP-3	3P DOUBLE BLOW	1300x2000x2100	800x1900x1960	2.2 kW	24	600 x4
BJ2400-D-QP-4	4P DOUBLE BLOW	1300x2500x2100	800x2400x1960	4.0 kW	32	820 x4
BJ2900-D-QP-5	5P DOUBLE BLOW	1300x3000x2100	800x2900x1960	4.0 kW	36	820 x4

ALSO AVAILABLE

- Cargo air showers and air shower tunnels for 100-150 persons / 10 min
- Corner and automatic-door configurations
- Left/right door orientation to your floor plan

Get factory pricing in 24h | WhatsApp +86 138 0000 0000 | info@bescolin.com

THIRD-PARTY INSPECTION (SGS / BV / TUV) WELCOME AT YOUR APPOINTED AGENCY